

999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake/Kabylake U-series Processor (15W)
- 2 * 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 32 GB
- 2 * USB2.0, 6 * USB3.0, 1 * COM, 1 * DP, 1 * HDMI, 2 * RJ45, 1 * Line in, 1 * Mic+Line out
- M/B Form Factor : UTX (117x112mm)
- DC-12V_40W Adapter

MB Model	<ul style="list-style-type: none"> - JNU792C-7100 _Core i3 Processor - JNU792V-3865 UTX _Celeron Processor
Part No.	<ul style="list-style-type: none"> - COM series: HBFCU792C-7100-B / HBFCU792CW-7100-B - TPM2.0 series: HBFCU792C-7100-T / HBFCU792CW-7100-T - VGA series: HBFCU792V-3865-B / HBFCU792VW-3865-B
BIOS	- AMI 16MB SMT Flash ROM
CPU/Chipset	<ul style="list-style-type: none"> - Intel® Skylake/Kabylake U-series Processor (MAX : TDP 15W) <p>Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.</p>
Memory	- 2 * 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 32 GB
Storage	<ul style="list-style-type: none"> - 1 * 2.5" SATA3 6Gb/s internal drive bay - 1 * Full-size mSATA/mini-PCI Express shared slot

Network	<ul style="list-style-type: none"> - 1 * Intel i211AT Gigabit LAN, 1 * Intel i219LM Gigabit LAN - 1 * Half-size mini-PCIE slot (for WIFI model installed)
Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB 3.0 ports / HBFCU792C-XXXX-B only - 2 * USB 3.0 ports , 2 * USB 2.0 / HBFCU792V-XXXX-B only - 1 * HDMI 1.4 (max. 4096 x 2304@24Hz resolution) - 1 * DP (max. 4096 x 2304@60Hz resolution) / HBFCU792C-XXXX-B only - 2 * RJ45 - 1 * Line-in, 1 * Mic+Line out (Realtek ALC662VD) - 2 * Antenna holes (WiFi only) - 1 * DC-In jack
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power button - 1 * Power LED , 1 * HDD LED - 2 * USB 2.0 , 2 * USB 3.0 - 1 * COM (RS232/422/485) / HBFCU792C(W)-XXXX-B only - 1 * VGA / HBFCU792V(W)-XXXX-B only
Power Source	<ul style="list-style-type: none"> - FSP AC TO DC Adapter / DC12V_3.3A_40W - AC 90~240V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVDS, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C
Dimensions	<ul style="list-style-type: none"> - 144 (W) x 116.9 (D) x 65 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 1.8KG - Gross Weight: 2.8KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	<ul style="list-style-type: none"> - 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	<ul style="list-style-type: none"> - 2 Year limited warranty