



569.00 EUR

incl. 19% VAT, plus [shipping](#)

- wlan !



- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor
- Intel® Coffee Lake-S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- 1\* Intel® I219-V Giga LAN + 1\* Intel® i225V 2.5Gb LAN
- Support 1\* SATA III (6Gb/s) & M.2 (M key 2242)
- 1\* M.2 E key Support CNVi
- 4\* RS232 (COM1/2 Support 5V/12V TTL, 4\* USB3.0
- Support HDMI/VGA /EDP (Option)
- DC 12~24V Input

|                |   |
|----------------|---|
| Model          | - HBJC501C8HV-H310<br>- HBJC501C8HVI-H310 (Wifi)  |
| CPU/Chipset    | - Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (TDP 35W)<br>- Intel® Coffee Lake-S H310 Chip   |
| BIOS           | - AMI 128MB SMT Flash ROM   |
| Memory         | - 2* DDR4 2133MHz up to 32GB  |
| Network        | - 1* Intel® I219-V GbE<br>- 1* Intel® I225-V 2.5GbE<br>- 1* WIFI2.4/5G + BT4.1 (M.2 E key)  |
| Graphics       | - 1* HDMI (Max. Resolution : 4096x2160@30Hz)<br>- 1* VGA (Max. Resolution: 1920x1080@60Hz)<br>- 1* eDP (Option, Max. Resolution: 4096x2304@60Hz)<br>- Support Dual Displays or Triple Displays with eDP |
| Storage        | - 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm)<br>- 1* M.2 (M-key 2242)  |
| Expansion slot | - 1* PCIe x4 slot<br>- 1* WIFI2.4/5G + BT4.1 (M.2 E key)  |
| Rear Panel I/O | - 4* USB3.0<br>- 1* HDMI<br>- 1* VGA<br>- 1* eDP<br>- 2* RJ45<br>- 4* RS232<br>- 1* Line-out +MIC<br>- 1* DC Jack<br>- 1* Power Button  |

---

|                    |   |
|--------------------|---|
| Front Panel I/O    | - NA  |
| Internal Connector | - NA  |
| Compliance         | - CE, FCC, RoHS, ErP Ready (option)   |
| Power Source       | - MB: DC 12~24V input<br>- Adapter: AC_90~240V/ DC_19V / 120W   |
| Temperature        | - Operating Temperature: -10 ~ 50° C<br>- Storage Temperature: -20 ~ 60° C<br>- Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Dimensions         | - System: 264 (W) x 199.4 (D) x 58 (H) mm   |
| OS Support         | - Windows 10, Linux   |