



379.00 EUR  
incl. 19% VAT, plus [shipping](#)

- N2930 BayTrail !
- 5x COM !
- miniITX !

- 1. Support Intel® Bay Trail N2930 SoC Processor
- 1\* DDR3L 1333MHz SO-DIMM up to 8GB
- 1\* 10/100/1000 Base-TX Ethernet Port
- 1\* HDMI, 1\* VGA, 1\* LVDS (co-layout with eDP)
- 5\* COM (COM1 support RS232/422/485), 1\* USB3.0, 7\* USB2.0
- 1\* M.2 M-key 2242/2280 (SATA interface), 1\* M.2 E-key 2230 (PCIe x1/USB2.0 interface), 1\* M.2 B-key 3042 (USB2.0 interface) W/SIM card holder
- 1\* SATA II (3Gb/s)
- Support 12V DC-in PWR
- 1\* PCIe x1 slot

Model	– MI97R30 – MI97R32 (Equipped with TPM2.0 model)
Form Factor	– Mini ITX (170 * 170mm)
Processor System	– Intel® Bay Trail N2930 SoC Processor – AMI Flash ROM BIOS
Expansion Slot	– 1* M.2 (E-key, 2230. USB2.0 & PCIe x1 interface) – 1* M.2 (B-key, 3042. USB2.0 interface) W/SIM card holder – 1* PCIe x1 slot
Memory	– 1* SO-DIMM DDR3L 1333MHz Single CH SDRAM up to 8GB

Graphics	<ul style="list-style-type: none"> <li>- Intel® HD Graphics, shared memory</li> <li>- 1* LVDS (Max Resolution: 1920x1200@60Hz)</li> <li>- 1* eDP (Max Resolution: 2560x1600@60Hz), Co-layout with LVDS</li> <li>- 1* VGA (Max Resolution: 1920x1080@60Hz)</li> <li>- 1* HDMI (Max Resolution: 1920x1200@60Hz)</li> </ul>
Ethernet	<ul style="list-style-type: none"> <li>- 1* Realtek RTL8119I GbE</li> </ul>
Audio	<ul style="list-style-type: none"> <li>- 4 channel HD audio: Realtek® ALC888S</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- 1* SATAII</li> <li>- 1* M.2 (M-key, 2242/2280. SATA interface)</li> </ul>
Rear I/O	<ul style="list-style-type: none"> <li>- 1* USB3.0</li> <li>- 3* USB2.0</li> <li>- 1* HDMI</li> <li>- 1* VGA</li> <li>- 1* PS/2</li> <li>- 1* RJ45</li> <li>- 2* COM (COM1 support RS232/422/485)</li> <li>- 1* Parallel</li> <li>- Line-out/MIC</li> <li>- 1* 12V DC-in PWR</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- 4* USB2.0</li> <li>- 3* COM (RS232)</li> <li>- 1* LVDS (co-layout with eDP)</li> <li>- 1* SATAII</li> <li>- 1* SIM card holder</li> <li>- 1* GPIO (8 bit)</li> <li>- 1* Audio Header (W/3W Amp.)</li> <li>- 1* SMBUS</li> <li>- 1* CPU FAN</li> <li>- 1* TPM2.0 onboard (MI97R32)</li> </ul>
Watchdog Timer	<ul style="list-style-type: none"> <li>- From Super I/O to drag RESETCON#</li> <li>- 256 segments (10sec ~ 255min)</li> </ul>
Power	<ul style="list-style-type: none"> <li>12V DC-in (2-pin PWR Con)</li> <li>- AT: Directly PWR on as Power input ready</li> <li>- ATX: Press Button to PWR on after Power input ready</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, REACH</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating: 0°C ~ 60°C(with 0.7m/s air flow)</li> <li>- Storage: -20°C ~ 85°C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>