



With standard full height bracket

With low-profile bracket

1189.00 EUR

incl. 19% VAT, plus [shipping](#)

- Up to 4096x2160/30fps !
- HDMI 1.4a !
- Low-profile PCI Express !
- Support 10-bit color depth !

AVerMedia CL314H1, the 1080p60 HDMI 4-Channel low profile video capture card, is equipped by four HDMI channels with the embedded audio input and supports astounding uncompressed real-time video capturing up to 1920 x 1080 60fps full HD resolution.

At the frame rate of 60 fps, CL314H1 can improve the quality of a wide range of media recorded for businesses, universities, broadcasting, and manufacturing facilities, which can eventually provide a more lifelike and smooth video playback experience.

With the AVerMedia Video Engine Technology inside, it can perform various video processing tasks such as frame rate conversion, hardware up/down scaling, de-interlacing, and so on without consuming the computing power of the target platform.

- Maximum input resolution up to 4096x2160/30fps
- Maximum capturing and recording up to 2-ch 4096x2160/30fps
- Low-profile PCI Express form factor
- Reduce the capture latency to shorten the time required for a full frame of image to be captured
- Support hardware up/down scaling, de-interlacing, and color space convert
- Support 10-bit color depth
- For 2-channel model: CL312H1

| | |
|-----------------------|--|
| Audio Interface | HDMI embedded PCM |
| Audio Format | Embedded HDMI, PCM |
| Audio Sampling Rate | 32/44.1/48KHz |
| Connector Type | HDMI Type A |
| Video Input Interface | HDMI*4 (HDMI 1.4a) YUV444: IYU2, AYUV, V410, Y410 YUV422: YUY2, YUYV, UYVY, V210, Y210 YUV420: I420, NV12, YV12 |
| Video Format | RGB: RGB565, RGB555, RGB24, RGB32, ARGB |
| Color Depth | 8-bit/ 10-bit |
| Channel No. | 4 channels |
| Max Input Resolution | 4096x2160 30fps 4096x2160 30fps (2ch) |
| Max Record Resolution | 1920x1080 60fps (4ch) |
| Encoding Mode | Software Encoding |
| Multi-Card Support | Yes |
| Supported OS | Windows 7, 8.1, 10 (32/64-Bit) Linux Kernel 2.6.14 and above (32/64-bit) |
| Form factor | PCIe Low Profile |
| Dimension (L x W) | 180 x 68.78 mm |
| Power Consumption | 15.0W < |
| Operating Temperature | 0°C ~ 50°C (by simulation) |
| Operating Humidity | 5% ~ 80% Relative Humidity |
| Safety Certification | FCC / CE |